

# Lutz Drum Pump Sets

- Now available -



## Electric or Air driven Drum Pump Set for Acids and Base solutions

### Consisting of:

Motor B36 with 16 ft cord or MD2 air motor, pump tube PP 39" sealless, high volume rotor, Hastelloy C shaft, PP Barrel Adaptor, 3/4" PP Nozzle, 8' PVC Hose, Hose Clamps, Wall Hanger



### Type of motor:

**B36**

**MD2 Air motor**

### Technical Data:

Max. Viscosity:	600 CPS	850 CPS
Max. Capacity:	13.5 GPM	13.5 GPM
Max. head:	31 ft.	31 ft.
Max. S.G.	1.4	1.6

Immersion depth:	39"	39"
Order-No.	0205-111-1	0205-111-2

Immersion depth:	47"	47"
Order-No.	0205-112-1	0205-112-2



## Electric or Air driven Drum Pump Set for Highly Corrosive Acids and Base solutions

### Consisting of:

Motor B55T-5 with 16 ft cord or MD2 air motor, pump tube PVDF 39" sealless, high volume rotor, Hastelloy C shaft, PP Barrel Adaptor, 1" PVDF Nozzle with swivel, 8' Chemical Hose, Hose Clamps, Wall Hanger



### Type of motor:

**B55T-5**

**MD2 Air motor**

### Technical Data:

Max. Viscosity:	500 CPS	850 CPS
Max. Capacity:	13.5 GPM	13.5 GPM
Max. head:	26 ft.	26 ft.
Max. S.G.	1.6	1.6

Immersion depth:	39"	39"
Order-No.	0205-201-1	0205-201-2

Immersion depth:	47"	47"
Order-No.	0205-202-1	0205-202-2



# Lutz Drum Pump Sets

- Now available -



## Electric or Air Driven Drum Pump Sets for Flammables, Hazardous Locations

**Consisting of:**

Motor ME I 6 EX, Class I Group C&D, Class II Groups F&G (Explosion Proof) with 16 ft cord or MD2 air motor, pump tube SS 39" sealless, high volume rotor, 1" SS Barrel Adaptor, 1" SS Nozzle with swivel, 8 ft. Conductive Chemical Tubing with Conductive Fittings, Ground & Bonding wires, Wall Hanger



Type of motor:	ME I 6 (Ex)	MD2 Air motor (Ex)
<b>Technical Data:</b>		
Max. Viscosity:	500 CPS	850 CPS
Max. Capacity:	18.5 GPM	18.5 GPM
Max. head:	33 ft.	33 ft.
Max. S.G.	1.3	1.6
Immersion depth:	39"	39"
Order-No.	0205-411-1	0205-411-2



## Electric or Air Driven Drum Pump Sets for Thin-bodied Oils and Diesel Fuel

**Consisting of:**

Motor B36 with 16 ft cord or MD2 air motor, pump tube ALU 39" sealless, high head impeller, 316 stainless steel shaft, PP Barrel Adaptor, 1" aluminium Nozzle with swivel, 8' PVC Hose, Hose Clamps, Wall Hanger



Type of motor:	B36	MD2 Air motor
<b>Technical Data:</b>		
Max. Viscosity:	500 CPS	1100 CPS
Max. Capacity:	15.9 GPM	15.9 GPM
Max. head:	68 ft.	68 ft.
Max. S.G.	1.4	1.6
Immersion depth:	39"	39"
Order-No.	0205-301-1	0205-301-2



**Lutz Pumps, Inc.**  
 1160 Beaver Ruin Road  
 Norcross, GA 30093-4898  
 Phone (770) 925-1222, (800) 843-3901  
 Fax: (770) 923-0334  
 e-mail: lutzpumps@mindspring.com · www.lutzpumps.com

Distributor: